

Creating Water Efficient Communities





Greyter filter options can be tailored to meet the needs of any project with options for simple filtration of rainwater, more demanding greywater applications and secondary treatment options to meet your projects water quality goals.

Greywater
Rainwater
Ground Water
Process Water
Combination Systems

- 350 micron Gravity Basin Filter for simple rainwater filtration and prescreening for greywater and other applications
- Dual parallel Pressure Filter Stations can be staged for multi-stage filtration and paralleled to handle increased load
- Pressure Filter Cartridges from 5 to 100 micron
- Intelligent sensing allows controller to notify when cartridges need to be cleaner or replaced
- Automatic divert when filters require maintenance
- Parallel design allows for maintenance without taking system off-line
- Durable, robust construction
- 2 Year Warranty
- Options Include:

Automatic backwash Additional post filtration In-tank treatment options Ultra-filtration UV Treatment



Bulletin Filter Option Overview Rev 10/14 © 2013 Greyter Water Systems Inc. All right reserved. Specifications are subject to change without notice.

Specifications

Gravity Basin Filter

Length: 94 cm (37") Width: 77.5 cm (30.5") Height: 133.5 cm (52.5")

Filtering Capacity: 750 LPM (198 GPM)

Weight: 31.75kg (70 lbs)



Long lasting LLDPE moulded shell.

Bolt down lid for access security.

Low maintenance.

Removable stainless steel filter basket (SSFB).

4" Grommet fittings supplied as standard.

Optional upgrade to 6" or 8" pipe grommets.

Slip fit pipe connection. No tools required.

Above or below grade installation.

Standalone or part of a rainwater harvesting or

greywater recycling system

Lift Station




- Watertight polyethylene housing.
- Maintenance access lid.
- Two submersible 1/2 hp greywater pumps.
- Double mechanical on/off float switches.
- Overload protection.
- Watertight electrical junction box.
- Solvent cement sockets.

Pressure Filter Station



- Two robust glass-reinforced polypropylene housings.
- Durable aluminium support.
- Four 2" manual valves.
- 3 way actuated filter by-pass valve.
- Pressure sensor.
- Two pressure indicators.



Greyter.com

Bulletin Filter Option Overview Rev 10, © 2013 Greyter Water Systems Inc. All right reserved. Specifications are subject to change without notice.